

Description	General Purpose		Heavy Duty
Series	NM	NC	NL
Max. Capacity, m ³ /h / USgpm	50/220	45/200	250/1100
Max. Pressure, bar / PSI	18/261	16/232	20/290
Max. Viscosity, cSt	7500	7500	250,000
Max. Temperature, °C / °F	150/302	150/302	250/480
Number of port / Max. port size	7/DN100	6/DN80	10/DN200
Ductile Iron	●	●	●
Carbon Steel	●	●	●
Stainless Steel	●	●	●
Packing Seal			●
Mechanical Seal	●	●	●
Jacket			●
180° opposite 180°	●	●	●
90° right angle 90°	●	●	●
Flanged Connection	●	●	●
Threaded Connection	●	●	●
Foot Mount	●	●	●
Driver Mount		●	
High Temperature	●	●	●
Abrasion			●
Corrosion			●
High Viscosity	●	●	●
Medium Viscosity	●	●	●
Low Viscosity	●	●	●

类别	通用		重载
系列	NM	NC	NL
最大流量, m ³ /h / USgpm	50/220	45/200	250/1100
最大压力, bar / PSI	18/261	16/232	20/290
最大粘度, cSt	7500	7500	250,000
最高温度, °C / °F	150/302	150/302	250/480
口径数量/最大口径	7/DN100	6/DN80	10/DN200
球铁	●	●	●
碳钢	●	●	●
不锈钢	●	●	●
填料密封			●
机械密封	●	●	●
夹套			●
180° 进出口	●	●	●
90° 进出口	●	●	●
法兰连接	●	●	●
螺纹连接	●	●	●
底脚固定	●	●	●
驱动端固定		●	
高温	●	●	●
磨蚀			●
腐蚀			●
高粘度	●	●	●
中粘度	●	●	●
低粘度	●	●	●